

# GASOLINE GENERATOR



Model		NK1500-E		NK1800-E		NK2500-E		NK3000-E	
Voltage	V	220	120/220	220	120/220	220	120/220	220	120/220
Frequency	Hz	50	60	50	60	50	60	50	60
Rated Output Power	kW	0.85	0.95	0.95	1.00	2.00	2.20	2.50	2.80
Max. Output Power	kW	1.00	1.10	1.10	1.20	2.30	2.50	2.80	3.00
Phase		1	1	1	1	1	1	1	1
Power Factor COS	∅	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Excitation Mode		Brush (AVR)		Brush (AVR)		Brush (AVR)		Brush (AVR)	
DC Output	V/Amps	12/8.3	12/8.3	12/8.3	12/8.3	12/8.3	12/8.3	12/8.3	12/8.3
Noise level (at 7m)	dB	74-77	74-77	74-77	74-77	74-77	74-77	74-77	74-77
Engine model		NK156F	NK156F	NK156F	NK156F	NK168FB	NK168FB	NK168FB	NK168FB
Max. Output Power	HP	3.0	3.0	3.0	3.0	6.5	6.5	6.5	6.5
Bore*Stroke	mm	56*40	56*40	56*40	56*40	68*54	68*54	68*54	68*54
Speed	rpm	3000	3600	3000	3600	3000	3600	3000	3600
Displacement	cc	98.5	98.5	98.5	98.5	196	196	196	196
Start system		Recoil or Electric		Recoil or Electric		Recoil or Electric		Recoil or Electric	
Fuel Capacity	L	6	6	6	6	15	15	15	15
Overall Dimension	mm	465x365x420		465x365x420		605x460x470		605x460x470	
Weight	Kg	26		27		46.5		47	
20GP/40GP/40HQ Loading	pcs	360/760/880		360/760/880		190/400/470		190/400/470	
Emission Compliance						Available also in Stage V			