

GASOLINE GENERATOR



Model		NK8000-E		NK9000-E		NK9500-E		NK10000-E	
Voltage	V	220	120/220	220	120/220	220	120/220	220	120/220
Frequency	Hz	50	60	50	60	50	60	50	60
Rated Output Power	kW	6.00	6.50	7.00	7.50	7.50	8.00	8.00	8.50
Max. Output Power	kW	6.50	7.00	7.50	8.00	8.00	8.50	8.50	9.00
Phase		1	1	1	1	1	1	1	1
Power Factor COS	∅	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Excitation Mode		Brush (AVR)		Brush (AVR)		Brush (AVR)		Brush (AVR)	
DC Output	V/Amps	12/8.3	12/8.3	12/8.3	12/8.3	12/8.3	12/8.3	12/8.3	12/8.3
Noise level (at 7m)	dB	74-77	74-77	74-77	74-77	74-77	74-77	74-77	74-77
Engine model		NK190F	NK190F	NK192FA	NK192FA	NK192FA	NK192FA	NK192FB	NK192FB
Max. Output Power	HP	15	15	16	16	16	16	17	17
Bore*Stroke	mm	90*66	90*66	92*66	92*66	92*66	92*66	92*69	92*69
Speed	rpm	3000	3600	3000	3600	3000	3600	3000	3600
Displacement	cc	420	420	438	438	438	438	458	458
Start system		Recoil or Electric		Recoil or Electric		Recoil or Electric		Recoil or Electric	
Fuel Capacity	L	25	25	25	25	25	25	25	25
Overall Dimension	mm	700x580x600		700x580x600		940x580x740		940x580x740	
Weight	Kg	92		95		95		100	
20GP/40GP/40HQ Loading	pcs	100/220/250		100/220/250		60/130/150		60/130/150	
Emission Compliance		Available also in Stage V							